

optibelt **MARATHON 2 M=S***

The precision ground MARATHON 2 M=S may be used in sets without measurement and is designed for high performance drives. It is characterized by its superior efficiency and reliability. It is not affected by slip and is extremely wear-resistant. Despite the high performance, multi-groove drives run with remarkably low vibration due to the precision ground profile.

Advantages

- Substantial cost savings
- High power transmission
- High operational safety
- Maintenance-free operation
- Extremely wear-resistant
- Quiet and smooth running

The Optibelt MARATHON 2 M=S is the maintenance-free option for all commercial vehicles.


Examples of Applications

- | | |
|------------------------------|--|
| Raw edge, moulded cogged | ■ high power transmission, small pulley diameters, high engine speeds |
| Fibre filled base | ■ high abrasion resistance, not affected by slip |
| Special fabric sub-structure | ■ high transverse rigidity with no loss of flexibility, more wear-resistant, longer service life |
| Polyester tension cord | ■ excellent tension behaviour, low stretch, maintenance-free |
| M=S version | ■ precision ground, can be used in sets without having to be measured (Matched Sets), highly precise section, smooth running |

***M=S can be used in sets without measurement**



MARATHON 2 M=S



- 1 Fabric
- 2 Chloroprene rubber compound with transversely oriented fibres
- 3 Low stretch polyester tension cord
- 4 Adhesive chloroprene rubber cushion compound
- 5 Special fabric
- 6 Chloroprene rubber compound with transversely oriented fibres

Sections:

AVX 13; AVP 13

Special sections:

AVX 10; AVP 10; AVX 15; AVX 17

Sizes:

AVX 13 from 700 to 2150 mm
 AVP 13 from 2018 to 2575 mm
 further sizes on request