

optibelt **RBK**

New engine design is putting an increasing emphasis on space saving. Small pulley diameters necessitating thin, flexible belts are often the result. Optibelt ribbed belts are ideal products for today's serpentine drives and operate all of the accessories quietly and smoothly.

Advantages

- High transmission ratios
- High power transmission
- Minimum slip
- Largely oil- and temperature-resistant
- Vibration-free and quiet
- Low stretch


In passenger cars, commercial vehicles and buses, Optibelt ribbed belts drive the ancillaries such as the generator, the air conditioning compressor, the power steering pump and the turbocharger smoothly and quietly.

Examples of Applications

- | | |
|--|---|
| Combination of trapezoidal ribs on a rubber core | ■ high power transmission, high wear resistance, quiet running |
| Single belt characteristic | ■ vibration-free as well as insensitive to pulsating running and intermittent loads |
| Polyester tension cord | ■ excellent tension behaviour, with low stretch |
| Low section height | ■ very flexible, extremely small pulley diameters, serpentine drives (using reverse bend idlers), good heat resistance, long life |



RBK



- 1 Fibre reinforced top surface: wear-resistant chloroprene rubber compound
- 2 Tension cord: low stretch polyester
- 3 Cushion rubber: high adhesion chloroprene cushion compound
- 4 Base: chloroprene rubber compound

Sections:

PJ; PK; DPK

Sizes:

- | | | | |
|-------|------|---------|---------|
| 2 PK | from | 786 to | 905 mm |
| 3 PK | from | 550 to | 1285 mm |
| 4 PK | from | 560 to | 1520 mm |
| 5 PK | from | 625 to | 2055 mm |
| 6 PK | from | 675 to | 2680 mm |
| 7 PK | from | 870 to | 2355 mm |
| 8 PK | from | 800 to | 2605 mm |
| 9 PK | from | 1200 to | 4145 mm |
| 10 PK | from | 1108 to | 2063 mm |
| 11 PK | from | 1515 to | 2055 mm |
| 12 PK | from | 1165 to | 2500 mm |
| 6 DPK | from | 1188 to | 1853 mm |
| 7 DPK | from | 1360 to | 1400 mm |

further sizes on request