

Technical Data Sheet

optibelt ALPHA FLEX H - RF

PU Timing Belt, Optionally with Fabric PAZ, Endless




Dimensions, Tolerances

Profile:	H
Tooth pitch t:	12.7 mm
Total thickness:	4.3 mm
Tooth height:	2.3 mm
Length tolerance:	±0.5 mm/m
Width tolerance:	±0.5 mm
Thickness tolerance:	±0.3 mm

Construction

Polyurethane:	Thermoplastic, 85 Shore A, transparent
Tension cord:	Stainless Steel, Ø 0.6 mm
Fabric, optional:	Polyamide, tooth side (PAZ), green



Specific nominal power transmittable per tooth

rpm, small idler n_k [1/min]	Spec. nom. power $P_{N\ spez}$ [W/mm]	rpm, small idler n_k [1/min]	Spec. nom. power $P_{N\ spez}$ [W/mm]	rpm, small idler n_k [1/min]	Spec. nom. power $P_{N\ spez}$ [W/mm]
0 ¹	0.000	1200	0.669	3600	1.407
20	0.019	1300	0.710	3800	1.453
40 ²	0.037	1400	0.749	4000	1.498
60	0.054	1500	0.787	4500	1.602
80 ³	0.070	1600 ⁷	0.824	5000	1.698
100	0.086	1700	0.860	5500	1.786
200 ⁴	0.159	1800	0.895	6000	1.867
300	0.224	1900	0.929	6500	1.940
400 ⁵	0.284	2000	0.962	7000	2.008
500	0.341	2200	1.027	7500	2.070
600	0.394	2400	1.088	8000	2.127
700	0.445	2600	1.147	8500	2.179
800 ⁶	0.493	2800	1.203	9000	2.227
900	0.540	3000	1.257	9500	2.268
1000	0.584	3200 ⁸	1.309	10000	2.307
1100	0.627	3400	1.359	$v_{max} = 60\text{ m/s}$	

Nominal power P_N

$$P_N = P_{N\ spez} \cdot z_k \cdot z_{eB} \cdot b / 10^3 \quad [\text{kW}]$$

$P_{N\ spez}$	Specific nominal power transmittable per tooth [W/mm]
z_k	Number of teeth, small idler
z_{eB}	Number of teeth in mesh, small idler, limited to $z_{eB\ max}$
$z_{eB\ max}$	12, max. allowable no. of teeth
b	belt width [mm]

Nominal torque M_N

$$M_N = P_N \cdot 9.55 \cdot 10^3 / n_k \quad [\text{Nm}]$$

n_k rpm, small idler [1/min]

Nominal tensile force F_N

$$F_N = F_{N\ spez} \cdot z_{eB} \cdot b \quad [\text{N}]$$

$$F_{N\ spez} = P_{N\ spez} \cdot 6 \cdot 10^4 / (n_k \cdot t) \quad [\text{N/mm}]$$

$F_{N\ spez}$	Specific nominal tensile force transmittable per tooth [N/mm]
t	Tooth pitch [mm]


¹ $F_{N\ spez}$ [N/mm] 4.600 ² 4.336 ³ 4.141 ⁴ 3.748 ⁵ 3.358 ⁶ 2.913 ⁷ 2.432 ⁸ 1.932

Cord tensile force, belt weight

Width code Belt width ¹ b [mm]	050	075	100	150	200	300	400
Cord breaking strength F_{Br} [N]	2720	4760	6800	10880	14600	22440	30240
Allowable tensile force ² F_{zul} [N]	680	1190	1700	2720	3650	5610	7560
Weight per metre [kg/m]	0.064	0.095	0.127	0.191	0.254	0.381	0.508

¹ Smaller and intermediate widths possible ² Allowable tensile force $F_{zul} = 25\%$ of cord breaking strength F_{Br}

Timing belt pulleys, inside and outside idlers



Minimum no. of teeth of the pulleys:	$z_{min} = 18$
Minimum pitch diameter of the pulleys:	$d_{w\ min} = 72.766\text{ mm}$
Plane, cylindrical idlers:	
Minimum-Ø of a plane inside idler:	$d_{min} = 65\text{ mm}$
Minimum-Ø of a plane outside idler:	$d_{min} = 80\text{ mm}$