

Technical Data Sheet

optibelt ALPHA LINEAR / V T10 - AR Polyurethane Timing Belt, Optionally With Fabric PAZ/PAR, Thermoplastic PU, Open-Ended / Endless Joined




Dimensions, Tolerances

Profile:	T10
Tooth pitch t:	10 mm
Total thickness:	4.5 mm
Tooth height:	2.5 mm
Tooth tip width:	3.5 mm
Tooth flank angle:	40°
Length tolerance:	±0.5 mm/m
Width tolerance:	±0.5 mm
Thickness tolerance:	±0.3 mm

Construction

Polyurethane:	Thermoplastic, 92 Shore A, white
Tension cord:	Aramid, Ø 0.7 mm
Fabric, optional:	Polyamide, tooth and back (PAZ/PAR), green



Specific nominal tensile force transmittable per tooth

Input speed n_1 [1/min]	Spec. nom. tensile force $F_{N\ spez}$ [N/mm]	Input speed n_1 [1/min]	Spec. nom. tensile force $F_{N\ spez}$ [N/mm]	Input speed n_1 [1/min]	Spec. nom. tensile force $F_{N\ spez}$ [N/mm]
0	5.200	1200	2.923	3600	2.037
20	5.024	1300	2.860	3800	1.993
40	4.879	1400	2.802	4000	1.950
60	4.755	1500	2.747	4500	1.853
80	4.646	1600	2.695	5000	1.766
100	4.551	1700	2.647	5500	1.687
200	4.189	1800	2.601	6000	1.615
300	3.936	1900	2.558	6500	1.549
400	3.742	2000	2.516	7000	1.487
500	3.585	2200	2.439	7500	1.430
600	3.452	2400	2.369	8000	1.376
700	3.338	2600	2.303	8500	1.325
800	3.237	2800	2.243	9000	1.278
900	3.147	3000	2.187	9500	1.233
1000	3.066	3200	2.134	10000	1.190
1100	2.991	3400	2.084	$v_{max} = 60$ m/s	

Nominal tensile force F_N

$$F_N = F_{N\ spez} \cdot z_{eB} \cdot b \quad [N]$$

$F_{N\ spez}$	Specific nominal tensile force transmittable per tooth [N/mm]
z_{eB}	Number of teeth in mesh, driver pulley, limited to $z_{eB\ max}$
$z_{eB\ max}$	ALPHA LINEAR: 12, ALPHA V: 6
b	Belt width [mm]

Nominal torque M_N

$$M_N = F_N \cdot d_{w1} / (2 \cdot 10^3) \quad [Nm]$$

$$d_{w1} = z_1 \cdot t / \pi \quad [mm]$$

d_{w1}	Pitch diameter, driver pulley [mm]
z_1	Number of teeth, driver pulley
t	Tooth pitch [mm]

Nominal power P_N

$$P_N = F_N \cdot z_1 \cdot t \cdot n_1 / (6 \cdot 10^7) \quad [kW]$$


n_1	Speed, driver pulley [1/min]
-------	------------------------------

Cord tensile force, minimum belt length, belt weight

Belt width ¹ b [mm]	16	25	32	50	75	100	150
F_{Br} [N], ALPHA LINEAR	5500	9900	13750	22550	35200	47300	72600
F_{zul} [N] ² , ALPHA LINEAR	1100	1980	2750	4510	7040	9460	14520
F_{zul} [N] ² , ALPHA V	550	990	1375	2255	3520	4730	7260
Minimum belt length [mm]	700	700	700	700	900	900	1100
Weight per metre [kg/m]	0.061	0.095	0.122	0.190	0.285	0.380	0.570

¹ Smaller and intermediate widths possible ² Allowable tensile force $F_{zul} = 20\% / 10\%$ (ALPHA LINEAR / V) of cord breaking strength F_{Br}

Timing belt pulleys, idlers, clamping plates



Minimum no. of teeth of the pulleys:	$z_{min} = 12$
Minimum pitch diameter of the pulleys:	$d_{w\ min} = 38.20$ mm
Minimum no. of teeth in mesh, clamp. plate:	$z_{CP\ min} = 6$
Minimum-Ø of a plane inside idler:	$d_{min} = 45$ mm
Minimum-Ø of a plane outside idler:	$d_{min} = 70$ mm