



Bezeichnung	Anzahl der Rillen	Ausführung	Max. Bohrung	Material	D _m (mm)	D _i (mm)	F (mm)	L (mm)	R (mm)	S (mm)	Taper buchse	
8PJ												
TB 8 PJ 56	8	2	28,00	GG	-	-	23,0	23,0	-	-	1108	
TB 8 PJ 63	8	2	28,00	GG	-	-	23,0	23,0	-	-	1108	
TB 8 PJ 71	8	2	28,00	GG	-	-	23,0	23,0	-	-	1108	
TB 8 PJ 75	8	2	28,00	GG	-	-	23,0	23,0	-	-	1108	
TB 8 PJ 80	8	3	42,00	GG	70,0	-	23,0	26,0	3,0	-	1610	
TB 8 PJ 85	8	3	42,00	GG	70,0	-	23,0	26,0	3,0	-	1610	
TB 8 PJ 90	8	3	42,00	GG	70,0	-	23,0	26,0	3,0	-	1610	
TB 8 PJ 95	8	3	42,00	GG	82,0	-	23,0	26,0	3,0	-	1610	
TB 8 PJ 100	8	3	42,00	GG	82,0	-	23,0	26,0	3,0	-	1610	
TB 8 PJ 106	8	3	42,00	GG	82,0	-	23,0	26,0	3,0	-	1610	
TB 8 PJ 112	8	3	42,00	GG	90,0	-	23,0	26,0	3,0	-	1610	
TB 8 PJ 118	8	3	42,00	GG	90,0	-	23,0	26,0	3,0	-	1610	
TB 8 PJ 125	8	3	42,00	GG	90,0	-	23,0	26,0	3,0	-	1610	
TB 8 PJ 132	8	3	42,00	GG	90,0	-	23,0	26,0	3,0	-	1610	
TB 8 PJ 140	8	3	42,00	GG	90,0	-	23,0	26,0	3,0	-	1610	
TB 8 PJ 160	8	6	50,00	GG	110,0	-	23,0	32,0	4,5	4,5	2012	
TB 8 PJ 180	8	6	50,00	GG	110,0	-	23,0	32,0	4,5	4,5	2012	
TB 8 PJ 190	8	6	50,00	GG	110,0	-	23,0	32,0	4,5	4,5	2012	
TB 8 PJ 200	8	6	50,00	GG	110,0	-	23,0	32,0	4,5	4,5	2012	
TB 8 PJ 212	8	6	50,00	GG	110,0	-	23,0	32,0	4,5	4,5	2012	
TB 8 PJ 224	8	6	50,00	GG	110,0	-	23,0	32,0	4,5	4,5	2012	
TB 8 PJ 250	8	6	50,00	GG	110,0	-	23,0	32,0	4,5	4,5	2012	
TB 8 PJ 280	8	7	50,00	GG	110,0	260,0	23,0	32,0	4,5	4,5	2012	
TB 8 PJ 315	8	7	50,00	GG	110,0	295,0	23,0	32,0	4,5	4,5	2012	
12PJ												
TB 12 PJ 63	12	4	28,00	GG	-	46,0	32,5	23,0	9,5	-	1108	
TB 12 PJ 71	12	4	28,00	GG	-	46,0	32,5	23,0	9,5	-	1108	
TB 12 PJ 75	12	4	42,00	GG	-	60,0	32,5	26,0	6,5	-	1610	
TB 12 PJ 80	12	4	42,00	GG	-	60,0	32,5	26,0	6,5	-	1610	
TB 12 PJ 85	12	4	42,00	GG	-	60,0	32,5	26,0	6,5	-	1610	
TB 12 PJ 90	12	4	42,00	GG	-	74,0	32,5	26,0	6,5	-	1610	
TB 12 PJ 95	12	4	42,00	GG	-	74,0	32,5	26,0	6,5	-	1610	
TB 12 PJ 100	12	4	42,00	GG	-	74,0	32,5	26,0	6,5	-	1610	
TB 12 PJ 106	12	4	42,00	GG	-	88,0	32,5	26,0	6,5	-	1610	
TB 12 PJ 112	12	4	42,00	GG	-	88,0	32,5	26,0	6,5	-	1610	
TB 12 PJ 118	12	4	50,00	GG	-	98,0	32,5	32,0	0,5	-	2012	
TB 12 PJ 125	12	4	50,00	GG	-	98,0	32,5	32,0	0,5	-	2012	
TB 12 PJ 132	12	4	65,00	GG	-	98,0	32,5	32,0	0,5	-	2012	
TB 12 PJ 140	12	3	65,00	GG	120,0	-	32,5	45,0	12,5	-	2517	
TB 12 PJ 160	12	3	65,00	GG	120,0	-	32,5	45,0	12,5	-	2517	
TB 12 PJ 180	12	6	65,00	GG	120,0	-	32,5	45,0	6,25	6,25	2517	
TB 12 PJ 190	12	6	65,00	GG	120,0	-	32,5	45,0	6,25	6,25	2517	
TB 12 PJ 200	12	6	65,00	GG	120,0	-	32,5	45,0	6,25	6,25	2517	
TB 12 PJ 212	12	6	65,00	GG	120,0	-	32,5	45,0	6,25	6,25	2517	

Bezeichnung	Anzahl der Rillen	Ausführung	Max. Bohrung	Material	D _m (mm)	D _i (mm)	F (mm)	L (mm)	R (mm)	S (mm)	Taper Buchse	
TB 12 PJ 224	12	6	65,00	GG	120,0	-	32,5	45,0	6,25	6,25	2517	
TB 12 PJ 250	12	6	65,00	GG	120,0	-	32,5	45,0	6,25	6,25	2517	
TB 12 PJ 280	12	7	65,00	GG	120,0	260,0	32,5	45,0	6,25	6,25	2517	
TB 12 PJ 315	12	7	65,00	GG	120,0	295,0	32,5	45,0	6,25	6,25	2517	
16PJ												
TB 16 PJ 71	16	2	32,00	GG	-	55,0	42,0	42,0	-	-	1215	
TB 16 PJ 75	16	4	42,00	GG	-	60,0	42,0	26,0	16,0	-	1610	
TB 16 PJ 80	16	4	42,00	GG	-	60,0	42,0	26,0	16,0	-	1610	
TB 16 PJ 85	16	4	42,00	GG	-	60,0	42,0	26,0	16,0	-	1610	
TB 16 PJ 90	16	4	42,00	GG	-	74,0	42,0	26,0	16,0	-	1610	
TB 16 PJ 95	16	4	42,00	GG	-	74,0	42,0	26,0	16,0	-	1610	
TB 16 PJ 100	16	4	42,00	GG	-	74,0	42,0	26,0	16,0	-	1610	
TB 16 PJ 106	16	4	42,00	GG	-	88,0	42,0	26,0	16,0	-	1610	
TB 16 PJ 112	16	4	42,00	GG	-	88,0	42,0	26,0	16,0	-	1610	
TB 16 PJ 118	16	4	50,00	GG	-	98,0	42,0	32,0	10,0	-	2012	
TB 16 PJ 125	16	4	50,00	GG	-	98,0	42,0	32,0	10,0	-	2012	
TB 16 PJ 132	16	4	50,00	GG	-	98,0	42,0	32,0	10,0	-	2012	
TB 16 PJ 140	16	3	65,00	GG	120,0	-	42,0	45,0	3,0	-	2517	
TB 16 PJ 160	16	3	65,00	GG	120,0	-	42,0	45,0	3,0	-	2517	
TB 16 PJ 180	16	6	65,00	GG	120,0	-	42,0	45,0	1,5	1,5	2517	
TB 16 PJ 190	16	6	65,00	GG	120,0	-	42,0	45,0	1,5	1,5	2517	
TB 16 PJ 200	16	6	65,00	GG	120,0	-	42,0	45,0	1,5	1,5	2517	
TB 16 PJ 212	16	6	65,00	GG	120,0	-	42,0	45,0	1,5	1,5	2517	
TB 16 PJ 224	16	6	65,00	GG	120,0	-	42,0	45,0	1,5	1,5	2517	
TB 16 PJ 250	16	6	65,00	GG	120,0	-	42,0	45,0	1,5	1,5	2517	
TB 16 PJ 280	16	7	65,00	GG	120,0	260,0	42,0	45,0	1,5	1,5	2517	
TB 16 PJ 315	16	7	65,00	GG	120,0	295,0	42,0	45,0	1,5	1,5	2517	
8PL												
TB 8 PL 90	8	4	42,00	GG	-	66,0	48,0	26,0	22,0	-	1108	
TB 8 PL 95	8	4	42,00	GG	-	71,0	48,0	26,0	22,0	-	1108	
TB 8 PL 106	8	4	42,00	GG	-	82,0	48,0	26,0	22,0	-	1108	
TB 8 PL 112	8	4	42,00	GG	-	88,0	48,0	26,0	16,0	-	1610	
TB 8 PL 125	8	4	50,00	GG	-	101,0	48,0	32,0	16,0	-	1610	
TB 8 PL 132	8	4	50,00	GG	-	108,0	48,0	32,0	16,0	-	1610	
TB 8 PL 140	8	4	65,00	GG	-	116,0	48,0	45,0	3,0	-	1610	
TB 8 PL 150	8	4	65,00	GG	-	126,0	48,0	45,0	3,0	-	1610	
TB 8 PL 160	8	4	65,00	GG	-	136,0	48,0	45,0	3,0	-	1610	
TB 8 PL 170	8	4	65,00	GG	-	146,0	48,0	45,0	3,0	-	1610	
TB 8 PL 180	8	8	65,00	GG	120,0	156,0	48,0	45,0	1,5	1,5	1610	
TB 8 PL 190	8	8	65,00	GG	120,0	166,0	48,0	45,0	1,5	1,5	1610	
TB 8 PL 200	8	8	65,00	GG	120,0	176,0	48,0	45,0	1,5	1,5	2012	
TB 8 PL 212	8	8	65,00	GG	120,0	188,0	48,0	45,0	1,5	1,5	2012	
TB 8 PL 224	8	8	65,00	GG	120,0	202,0	48,0	45,0	1,5	1,5	2012	
TB 8 PL 250	8	7	75,00	GG	146,0	228,0	48,0	52,0	2,0	2,0	2012	
TB 8 PL 280	8	7	75,00	GG	146,0	256,0	48,0	52,0	2,0	2,0	2012	
TB 8 PL 315	8	7	75,00	GG	146,0	285,0	48,0	52,0	2,0	2,0	2012	
12PL												
TB 12 PL 75	12	4	32,00	GG	-	56,0	67,0	42,0	25,0	-	1215	
TB 12 PL 80	12	4	32,00	GG	-	56,0	67,0	42,0	25,0	-	1215	
TB 12 PL 85	12	4	32,00	GG	-	61,0	67,0	42,0	25,0	-	1215	
TB 12 PL 90	12	4	42,00	GG	-	66,0	67,0	42,0	25,0	-	1615	
TB 12 PL 95	12	4	42,00	GG	-	71,0	67,0	42,0	25,0	-	1615	


Bezeichnung	Anzahl der Rillen	Ausführung	Max. Bohrung	Material	D _m (mm)	D _i (mm)	F (mm)	L (mm)	R (mm)	S (mm)	Taper buchse
TB 12 PL 100	12	4	50,00	GG	-	79,0	67,0	32,0	35,0	-	2012
TB 12 PL 106	12	5	50,00	GG	-	82,0	67,0	32,0	35,0	-	2012
TB 12 PL 112	12	5	50,00	GG	-	88,0	67,0	32,0	35,0	-	2012
TB 12 PL 125	12	5	65,00	GG	-	101,0	67,0	45,0	11,0	11,0	2517
TB 12 PL 132	12	5	65,00	GG	-	108,0	67,0	45,0	11,0	11,0	2517
TB 12 PL 140	12	5	65,00	GG	-	116,0	67,0	45,0	11,0	11,0	2517
TB 12 PL 150	12	5	65,00	GG	-	126,0	67,0	45,0	11,0	11,0	2517
TB 12 PL 160	12	5	65,00	GG	-	136,0	67,0	45,0	11,0	11,0	2517
TB 12 PL 170	12	5	65,00	GG	-	146,0	67,0	45,0	11,0	11,0	2517
TB 12 PL 180	12	8	65,00	GG	120,0	156,0	67,0	45,0	11,0	11,0	2517
TB 12 PL 190	12	8	65,00	GG	120,0	166,0	67,0	45,0	11,0	11,0	2517
TB 12 PL 200	12	8	75,00	GG	146,0	176,0	67,0	52,0	7,5	7,5	3020
TB 12 PL 212	12	8	75,00	GG	146,0	188,0	67,0	52,0	7,5	7,5	3020
TB 12 PL 224	12	8	75,00	GG	146,0	202,0	67,0	52,0	7,5	7,5	3020
TB 12 PL 250	12	8	75,00	GG	146,0	228,0	67,0	52,0	7,5	7,5	3020
TB 12 PL 280	12	8	75,00	GG	146,0	256,0	67,0	52,0	7,5	7,5	3020
16PL											
TB 16 PL 85	16	5	32,00	GG	-	61,0	86,0	42,0	22,0	22,0	1215
TB 16 PL 90	16	5	42,00	GG	-	66,0	86,0	42,0	22,0	22,0	1615
TB 16 PL 95	16	5	42,00	GG	-	71,0	86,0	42,0	22,0	22,0	1615
TB 16 PL 100	16	5	50,00	GG	-	79,0	86,0	32,0	27,0	27,0	2012
TB 16 PL 106	16	5	50,00	GG	-	82,0	86,0	32,0	27,0	27,0	2012
TB 16 PL 112	16	5	50,00	GG	-	88,0	86,0	32,0	27,0	27,0	2012
TB 16 PL 125	16	5	65,00	GG	-	101,0	86,0	45,0	20,5	20,5	2517
TB 16 PL 132	16	5	65,00	GG	-	108,0	86,0	45,0	20,5	20,5	2517
TB 16 PL 140	16	5	65,00	GG	-	116,0	86,0	45,0	20,5	20,5	2517
TB 16 PL 150	16	5	65,00	GG	-	126,0	86,0	45,0	20,5	20,5	2517
TB 16 PL 160	16	5	75,00	GG	-	136,0	86,0	52,0	17,0	17,0	3020
TB 16 PL 170	16	5	75,00	GG	-	146,0	86,0	52,0	17,0	17,0	3020
TB 16 PL 180	16	5	75,00	GG	-	156,0	86,0	52,0	17,0	17,0	3020
TB 16 PL 190	16	8	75,00	GG	146,0	166,0	86,0	52,0	17,0	17,0	3020
TB 16 PL 200	16	8	75,00	GG	146,0	176,0	86,0	52,0	17,0	17,0	3020
TB 16 PL 212	16	8	75,00	GG	146,0	188,0	86,0	52,0	17,0	17,0	3020
TB 16 PL 224	16	8	75,00	GG	146,0	202,0	86,0	52,0	17,0	17,0	3020
TB 16 PL 250	16	7	90,00	GG	178,0	228,0	86,0	89,0	1,5	1,5	3535
TB 16 PL 280	16	7	90,00	GG	178,0	256,0	86,0	89,0	1,5	1,5	3535
TB 16 PL 315	16	7	90,00	GG	178,0	285,0	86,0	89,0	1,5	1,5	3535




Ausf. 1




Ausf. 2



Ausf. 3



Ausf. 4



Ausf. VB

Bezeichnung	Anzahl der Rillen	Ausführung	Material	d_b (mm)	b_2 (mm)	B (mm)	N (mm)	D (mm)	Taperbuche
4PJ									
TB 4 PJ 47,5	4	1	GG	47,5	13	23	23	47,5	1008
TB 4 PJ 52,5	4	1	GG	52,5	13	23	23	47,5	1008
TB 4 PJ 57,5	4	1	GG	57,5	13	23	23	54,0	1108
TB 4 PJ 62,5	4	1	GG	62,5	13	23	23	54,0	1108
TB 4 PJ 67,5	4	1	GG	67,5	13	23	23	54,0	1108
TB 4 PJ 72,5	4	1	GG	72,5	13	23	23	54,0	1108
TB 4 PJ 77,5	4	1	GG	77,5	13	26	26	70,0	1210
TB 4 PJ 82,5	4	1	GG	82,5	13	26	26	78,0	1210
TB 4 PJ 87,5	4	1	GG	87,5	13	26	26	78,0	1210
TB 4 PJ 92,5	4	1	GG	92,5	13	26	26	78,0	1210
TB 4 PJ 97,5	4	1	GG	97,5	13	26	26	78,0	1210
TB 4 PJ 102,5	4	1	GG	102,5	13	26	26	85,0	1610
TB 4 PJ 107,5	4	1	GG	107,5	13	26	26	85,0	1610
TB 4 PJ 112,5	4	1	GG	112,5	13	26	26	85,0	1610
TB 4 PJ 117,5	4	1	GG	117,5	13	26	26	85,0	1610
TB 4 PJ 122,5	4	1	GG	122,5	13	26	26	85,0	1610
TB 4 PJ 127,5	4	1	GG	127,5	13	26	26	85,0	1610
TB 4 PJ 137,5	4	1	GG	137,5	13	26	26	85,0	1610
TB 4 PJ 152,5	4	1	GG	152,5	13	26	26	85,0	1610
TB 4 PJ 162,5	4	1	GG	162,5	13	26	26	85,0	1610
TB 4 PJ 172,5	4	1	GG	172,5	13	26	26	85,0	1610
TB 4 PJ 182,5	4	1	GG	182,5	13	26	26	85,0	1610
TB 4 PJ 192,5	4	1	GG	192,5	13	26	26	85,0	1610
TB 4 PJ 202,5	4	1	GG	202,5	13	33	33	100,0	2012
TB 4 PJ 222,5	4	1	GG	222,5	13	33	33	100,0	2012
8PJ									
TB 8 PJ 47,5	8	4	GG	47,5	23	23	23	-	1008
TB 8 PJ 52,5	8	4	GG	52,5	23	23	23	-	1008
TB 8 PJ 57,5	8	4	GG	57,5	23	23	23	-	1108
TB 8 PJ 62,5	8	4	GG	62,5	23	23	23	-	1108
TB 8 PJ 67,5	8	4	GG	67,5	23	23	23	-	1108
TB 8 PJ 72,5	8	4	GG	72,5	23	23	23	-	1108
TB 8 PJ 77,5	8	1	GG	77,5	23	26	26	70	1210
TB 8 PJ 82,5	8	1	GG	82,5	23	26	26	78	1210
TB 8 PJ 87,5	8	1	GG	87,5	23	26	26	78	1210
TB 8 PJ 92,5	8	1	GG	92,5	23	26	26	78	1210
TB 8 PJ 97,5	8	1	GG	97,5	23	26	26	78	1210
TB 8 PJ 102,5	8	1	GG	102,5	23	26	26	85	1610
TB 8 PJ 107,5	8	1	GG	107,5	23	26	26	85	1610
TB 8 PJ 112,5	8	1	GG	112,5	23	26	26	85	1610
TB 8 PJ 117,5	8	1	GG	117,5	23	26	26	85	1610
TB 8 PJ 122,5	8	1	GG	122,5	23	26	26	85	1610
TB 8 PJ 127,5	8	1	GG	127,5	23	26	26	85	1610
TB 8 PJ 137,5	8	1	GG	137,5	23	26	26	85	1610

Bezeichnung	Anzahl der Rillen	Ausführung	Material	d _e (mm)	b ₂ (mm)	B (mm)	N (mm)	D (mm)	Taperbuchse
TB 8 PJ 152,5	8	1	GG	152,5	23	26	26	85	1610
TB 8 PJ 162,5	8	1	GG	162,5	23	26	26	85	1610
TB 8 PJ 172,5	8	1	GG	172,5	23	26	26	85	1610
TB 8 PJ 182,5	8	1	GG	182,5	23	26	26	85	1610
TB 8 PJ 192,5	8	1	GG	192,5	23	26	26	85	1610
TB 8 PJ 202,5	8	1	GG	202,5	23	33	33	100	2012
TB 8 PJ 222,5	8	1	GG	222,5	23	33	33	100	2012
12PJ									
TB 12 PJ 62,5	12	2	GG	62,5	32	32	23	50	1108
TB 12 PJ 67,5	12	2	GG	67,5	32	32	23	50	1108
TB 12 PJ 72,5	12	2	GG	72,5	32	32	26	50	1108
TB 12 PJ 77,5	12	2	GG	77,5	32	32	26	62	1210
TB 12 PJ 82,5	12	2	GG	82,5	32	32	26	62	1210
TB 12 PJ 87,5	12	2	GG	87,5	32	32	26	70	1610
TB 12 PJ 92,5	12	2	GG	92,5	32	32	26	70	1610
TB 12 PJ 97,5	12	2	GG	97,5	32	32	26	70	1610
TB 12 PJ 102,5	12	2	GG	102,5	32	32	26	70	1610
TB 12 PJ 107,5	12	2	GG	107,5	32	32	26	70	1610
TB 12 PJ 112,5	12	2	GG	112,5	32	32	33	70	1610
TB 12 PJ 117,5	12	2	GG	117,5	32	32	33	70	1610
TB 12 PJ 122,5	12	2	GG	122,5	32	32	33	70	1610
TB 12 PJ 127,5	12	1	GG	127,5	32	32	33	100	2012
TB 12 PJ 137,5	12	1	GG	137,5	32	32	33	100	2012
TB 12 PJ 152,5	12	1	GG	152,5	32	32	33	100	2012
TB 12 PJ 162,5	12	1	GG	162,5	32	32	33	100	2012
TB 12 PJ 172,5	12	1	GG	172,5	32	32	33	100	2012
TB 12 PJ 182,5	12	1	GG	182,5	32	46	46	110	2517
TB 12 PJ 192,5	12	1	GG	192,5	32	46	46	110	2517
TB 12 PJ 202,5	12	1	GG	202,5	32	46	46	110	2517
TB 12 PJ 222,5	12	1	GG	222,5	32	46	46	110	2517
16PJ									
TB 16 PJ 62,5	16	2	GG	62,5	41	41	23	50	1108
TB 16 PJ 67,5	16	2	GG	67,5	41	41	23	50	1108
TB 16 PJ 72,5	16	2	GG	72,5	41	41	26	62	1210
TB 16 PJ 77,5	16	2	GG	77,5	41	41	26	62	1210
TB 16 PJ 82,5	16	2	GG	82,5	41	41	26	62	1210
TB 16 PJ 87,5	16	2	GG	87,5	41	41	26	70	1610
TB 16 PJ 92,5	16	2	GG	92,5	41	41	26	70	1610
TB 16 PJ 97,5	16	2	GG	97,5	41	41	26	70	1610
TB 16 PJ 102,5	16	2	GG	102,5	41	41	26	70	1610
TB 16 PJ 107,5	16	2	GG	107,5	41	41	26	70	1610
TB 16 PJ 112,5	16	2	GG	112,5	41	41	33	85	2012
TB 16 PJ 117,5	16	2	GG	117,5	41	41	33	85	2012
TB 16 PJ 122,5	16	2	GG	122,5	41	41	33	85	2012
TB 16 PJ 127,5	16	2	GG	127,5	41	41	33	85	2012
TB 16 PJ 137,5	16	2	GG	137,5	41	41	33	85	2012
TB 16 PJ 152,5	16	2	GG	152,5	41	41	33	85	2012
TB 16 PJ 162,5	16	2	GG	162,5	41	41	33	85	2012
TB 16 PJ 172,5	16	2	GG	172,5	41	41	33	85	2012
TB 16 PJ 182,5	16	1	GG	182,5	41	46	46	110	2517
TB 16 PJ 192,5	16	1	GG	192,5	41	46	46	110	2517
TB 16 PJ 202,5	16	1	GG	202,5	41	46	46	110	2517

Bezeichnung	Anzahl der Rillen	Ausführung	Material	d _b (mm)	b ₂ (mm)	B (mm)	N (mm)	D (mm)	Taperbuchse
TB 16 PJ 222,5	16	1	GG	222,5	41	46	46	110	2517
6PL									
TB 6 PL 78	6	2	GG	78,0	33	33	26	62	1210
TB 6 PL 83	6	2	GG	83,0	33	33	26	62	1210
TB 6 PL 88	6	2	GG	88,0	33	33	26	70	1610
TB 6 PL 93	6	2	GG	93,0	33	33	26	70	1610
TB 6 PL 98	6	2	GG	98,0	33	33	26	70	1610
TB 6 PL 103	6	2	GG	103,0	33	33	26	70	1610
TB 6 PL 108	6	2	GG	108,0	33	33	26	70	1610
TB 6 PL 113	6	2	GG	113,0	33	33	26	70	1610
TB 6 PL 118	6	2	GG	118,0	33	33	26	70	1610
TB 6 PL 123	6	4	GG	123,0	33	33	33	-	2012
TB 6 PL 133	6	4	GG	133,0	33	33	33	-	2012
TB 6 PL 148	6	4	GG	148,0	33	33	33	-	2012
TB 6 PL 158	6	4	GG	158,0	33	33	33	-	2012
TB 6 PL 168	6	4	GG	168,0	33	33	33	-	2012
TB 6 PL 178	6	1	GG	178,0	33	46	46	110	2517
TB 6 PL 188	6	1	GG	188,0	33	46	46	110	2517
TB 6 PL 198	6	1	GG	198,0	33	46	46	110	2517
TB 6 PL 218	6	1	GG	218,0	33	46	46	110	2517
TB 6 PL 238	6	1	GG	238,0	33	46	46	110	2517
TB 6 PL 258	6	1	GG	258,0	33	46	46	110	2517
TB 6 PL 278	6	1	GG	278,0	33	46	46	110	2517
TB 6 PL 298	6	1	GG	298,0	33	46	46	110	2517
TB 6 PL 318	6	1	GG	318,0	33	46	46	110	2517
TB 6 PL 348	6	1	GG	348,0	33	46	46	110	2517
TB 6 PL 388	6	1	GG	388,0	33	46	46	110	2517
8PL									
TB 8 PL 78	8	2	GG	78,0	42	42	26	62	1210
TB 8 PL 83	8	2	GG	83,0	42	42	26	62	1210
TB 8 PL 88	8	2	GG	88,0	42	42	26	70	1610
TB 8 PL 93	8	2	GG	93,0	42	42	26	70	1610
TB 8 PL 98	8	2	GG	98,0	42	42	26	70	1610
TB 8 PL 103	8	2	GG	103,0	42	42	33	85	2012
TB 8 PL 108	8	2	GG	108,0	42	42	33	85	2012
TB 8 PL 113	8	2	GG	113,0	42	42	33	85	2012
TB 8 PL 118	8	2	GG	118,0	42	42	33	85	2012
TB 8 PL 123	8	2	GG	123,0	42	42	33	85	2012
TB 8 PL 133	8	2	GG	133,0	42	42	33	85	2012
TB 8 PL 148	8	2	GG	148,0	42	42	33	85	2012
TB 8 PL 158	8	2	GG	158,0	42	42	33	85	2012
TB 8 PL 168	8	2	GG	168,0	42	42	33	85	2012
TB 8 PL 178	8	1	GG	178,0	42	46	46	110	2517
TB 8 PL 188	8	1	GG	188,0	42	46	46	110	2517
TB 8 PL 198	8	1	GG	198,0	42	46	46	110	2517
TB 8 PL 218	8	1	GG	218,0	42	46	46	110	2517
TB 8 PL 238	8	1	GG	238,0	42	46	46	110	2517
TB 8 PL 258	8	1	GG	258,0	42	46	46	110	2517
TB 8 PL 278	8	1	GG	278,0	42	46	46	110	2517
TB 8 PL 298	8	1	GG	298,0	42	46	46	110	2517
TB 8 PL 318	8	1	GG	318,0	42	46	46	110	2517
TB 8 PL 348	8	1	GG	348,0	42	46	46	110	2517

optibelt RBS Keilrippenscheiben für Taper-Buchsen
Sondergrößen im Profil PL



Bezeichnung	Anzahl der Rillen	Ausführung	Material	d _e (mm)	b ₂ (mm)	B (mm)	N (mm)	D (mm)	Taperbuchse	
TB 8 PL 388	8	1	GG	388,0	42	46	46	110	2517	
10PL										
TB 10 PL 88	10	3	GG	88,0	53	53	26	70	1610	
TB 10 PL 93	10	3	GG	93,0	53	53	26	70	1610	
TB 10 PL 98	10	3	GG	98,0	53	53	26	70	1610	
TB 10 PL 103	10	2	GG	103,0	53	53	33	85	2012	
TB 10 PL 108	10	2	GG	108,0	53	53	33	85	2012	
TB 10 PL 113	10	2	GG	113,0	53	53	33	85	2012	
TB 10 PL 118	10	2	GG	118,0	53	53	33	85	2012	
TB 10 PL 123	10	2	GG	123,0	53	53	33	85	2012	
TB 10 PL 133	10	2	GG	133,0	53	53	33	85	2012	
TB 10 PL 148	10	2	GG	148,0	53	53	33	85	2012	
TB 10 PL 158	10	2	GG	158,0	53	53	33	85	2012	
TB 10 PL 168	10	2	GG	168,0	53	53	33	85	2012	
TB 10 PL 178	10	2	GG	178,0	53	53	46	105	2517	
TB 10 PL 188	10	2	GG	188,0	53	53	46	105	2517	
TB 10 PL 198	10	2	GG	198,0	53	53	46	105	2517	
TB 10 PL 218	10	2	GG	218,0	53	53	46	105	2517	
TB 10 PL 238	10	2	GG	238,0	53	53	46	105	2517	
TB 10 PL 258	10	2	GG	258,0	53	53	46	105	2517	
TB 10 PL 278	10	2	GG	278,0	53	53	46	105	2517	
TB 10 PL 298	10	2	GG	298,0	53	53	46	105	2517	
TB 10 PL 318	10	2	GG	318,0	53	53	46	105	2517	
TB 10 PL 348	10	2	GG	348,0	53	53	46	105	2517	
TB 10 PL 388	10	2	GG	388,0	53	53	46	105	2517	
12PL										
TB 12 PL 88	12	3	GG	88,0	62	62	26	70	1610	
TB 12 PL 93	12	3	GG	93,0	62	62	26	70	1610	
TB 12 PL 98	12	3	GG	98,0	62	62	26	70	1610	
TB 12 PL 103	12	3	GG	103,0	62	62	33	85	2012	
TB 12 PL 108	12	3	GG	108,0	62	62	33	85	2012	
TB 12 PL 113	12	3	GG	113,0	62	62	33	85	2012	
TB 12 PL 118	12	3	GG	118,0	62	62	33	85	2012	
TB 12 PL 123	12	3	GG	123,0	62	62	33	85	2012	
TB 12 PL 133	12	3	GG	133,0	62	62	33	85	2012	
TB 12 PL 148	12	2	GG	148,0	62	62	46	105	2517	
TB 12 PL 158	12	2	GG	158,0	62	62	46	105	2517	
TB 12 PL 168	12	2	GG	168,0	62	62	46	105	2517	
TB 12 PL 178	12	2	GG	178,0	62	62	46	105	2517	
TB 12 PL 188	12	2	GG	188,0	62	62	46	105	2517	
TB 12 PL 198	12	2	GG	198,0	62	62	46	105	2517	
TB 12 PL 218	12	2	GG	218,0	62	62	46	105	2517	
TB 12 PL 238	12	2	GG	238,0	62	62	52	130	3020	
TB 12 PL 258	12	2	GG	258,0	62	62	52	130	3020	
TB 12 PL 278	12	2	GG	278,0	62	62	52	130	3020	
TB 12 PL 298	12	2	GG	298,0	62	62	52	130	3020	
TB 12 PL 318	12	2	GG	318,0	62	62	52	130	3020	
TB 12 PL 348	12	2	GG	348,0	62	62	52	130	3020	
TB 12 PL 388	12	2	GG	388,0	62	62	52	130	3020	
16PL										
TB 16 PL 103	16	3	GG	103,0	80	80	33	85	2012	
TB 16 PL 108	16	3	GG	108,0	80	80	33	85	2012	

Bezeichnung	Anzahl der Rillen	Ausführung	Material	d _b (mm)	b ₂ (mm)	B (mm)	N (mm)	D (mm)	Taperbuchse
TB 16 PL 113	16	3	GG	113,0	80	80	33	85	2012
TB 16 PL 118	16	3	GG	118,0	80	80	33	85	2012
TB 16 PL 123	16	3	GG	123,0	80	80	33	85	2012
TB 16 PL 133	16	3	GG	133,0	80	80	33	85	2012
TB 16 PL 148	16	3	GG	148,0	80	80	46	105	2517
TB 16 PL 158	16	3	GG	158,0	80	80	46	105	2517
TB 16 PL 168	16	3	GG	168,0	80	80	46	105	2517
TB 16 PL 178	16	3	GG	178,0	80	80	46	105	2517
TB 16 PL 188	16	3	GG	188,0	80	80	46	105	2517
TB 16 PL 198	16	3	GG	198,0	80	80	46	105	2517
TB 16 PL 218	16	3	GG	218,0	80	80	46	105	2517
TB 16 PL 238	16	3	GG	238,0	80	80	52	130	3020
TB 16 PL 258	16	3	GG	258,0	80	80	52	130	3020
TB 16 PL 278	16	3	GG	278,0	80	80	52	130	3020
TB 16 PL 298	16	3	GG	298,0	80	80	52	130	3020
TB 16 PL 318	16	3	GG	318,0	80	80	52	130	3020
TB 16 PL 348	16	3	GG	348,0	80	80	52	130	3020
TB 16 PL 388	16	3	GG	388,0	80	80	52	130	3020

Taper-Buchse	1008	1108	1210	1610	2012	2517	3020	3535
Bohrung d ₂ (mm) von... bis...	10-25	10-28	11-32	14-42	14-50	16-65	25-75	35-90

GG = Grauguss Weitere Abmessungen auf Anfrage. Fertigungstechnische Änderungen vorbehalten.
Bohrungsdurchmesser d₂ siehe Seite 4.

**optibelt RBS Keilrippenscheiben für zylindrische Bohrung
Sondergrößen im Profil PJ**

Bezeichnung	Anzahl der Rillen	Ausführung	Material	d _b (mm)	b ₁ (mm)	B (mm)	D (mm)	Vorbohrung d (mm)	Fertigbohrung d _{max} (mm)	Gewicht (=kg)
4PJ										
4 PJ 22,5	4	VB	GG	22,5	13	20	25	8	12	0,045
4 PJ 27,5	4	VB	GG	27,5	13	20	30	8	14	0,070
4 PJ 32,5	4	VB	GG	32,5	13	20	35	8	18	0,100
4 PJ 37,5	4	VB	GG	37,5	13	20	40	8	20	0,135
4 PJ 42,5	4	VB	GG	42,5	13	20	45	8	22	0,180
8PJ										
8 PJ 22,5	8	VB	GG	22,5	23	30	25	8	12	0,063
8 PJ 27,5	8	VB	GG	27,5	23	30	30	8	14	0,100
8 PJ 32,5	8	VB	GG	32,5	23	30	35	8	18	0,150
8 PJ 37,5	8	VB	GG	37,5	23	30	40	8	20	0,200
8 PJ 42,5	8	VB	GG	42,5	23	30	45	8	22	0,265
12PJ										
12 PJ 22,5	12	VB	GG	22,5	32	40	25	8	12	0,086
12 PJ 27,5	12	VB	GG	27,5	32	40	30	8	14	0,140
12 PJ 32,5	12	VB	GG	32,5	32	40	35	8	18	0,200
12 PJ 37,5	12	VB	GG	37,5	32	40	40	8	20	0,280
12 PJ 42,5	12	VB	GG	42,5	32	40	45	8	22	0,360

GG = Grauguss Weitere Abmessungen auf Anfrage. Fertigungstechnische Änderungen vorbehalten.