



Profiles:

Y/6, 8, Z/10, A/13, B/17, 20, C/22, 25, D/32, E/40

optibelt OPTIMAT OE

OPEN ENDED V-BELTS punched

	Y/6	8	Z/10	A/13	B/17	20	C/22	25	D/32	E/40
Height of belt h [mm]	4,00	5,00	6,00	8,00	11,00	12,50	14,00	16,00	20,00	25,00
Width of belt b [mm]	6,00	8,00	10,00	13,00	17,00	20,00	22,00	25,00	32,00	40,00
Weight [kg/m]	0,030	0,050	0,070	0,120	0,200	0,270	0,340	0,440	0,680	1,000
Max. fabrication length [mm]	50000	50000	50000	50000	50000	50000	50000	50000	50000	50000
Minimum pulley diameter [mm]	50	63	80	100	140	180	224	250	355	500
Plate connectors weight [kg/100 item]	0,1	0,2	0,3	0,5	0,8	1,4	1,7	2,1	5,0	10,0
Link connectors weight [kg/100 items]	-	-	0,7	1,8	2,9	4,6	5,7	-	-	-

- Non stock items
- not available
- Stock items

Unpunched: no surcharge
 Construction „S“ with black chloroprene top surface: 10% surcharge.

Surcharge for short lengths
 under 10 m: 70%
 from 10 to 49 m: 25%

Ordering example OPTIMAT OE: O-OE 6 Standard / green

Profile	Weight per meter (kg/m)	Standard / green	Polyester / red	Plate connector	Link connector
Y/6	0,030	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-
8	0,050	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-
Z/10	0,070	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
A/13	0,120	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
B/17	0,200	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
20	0,270	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
C/22	0,340	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
25	0,440	<input type="checkbox"/>	•	<input type="checkbox"/>	-
D/32	0,680	<input type="checkbox"/>	•	<input type="checkbox"/>	-
E/40	1,000	•	•	<input type="checkbox"/>	-